

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Thinner C

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Thinner, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Srbija d.o.o.
Patrijarha Pavla 1
22310 Šimanovci
Srbija
Telephone : +381 22 21 55 777
Telefax : +381 22 21 55 780
E-mail address of person : ehs@rs.sika.com
responsible for the SDS

1.4 Emergency telephone number

National Toxicology Institute -
+381 11 360 84 40 (toxicologist on duty - 0- 24h)

SECTION 2: Hazards identification

Type of product : Mixture

2.1 Classification of the substance or mixture

Classification (according to CLP/GHS)

Flammable liquids, Category 3

H226: Flammable liquid and vapour.

Acute toxicity, Category 4

H332: Harmful if inhaled.

Acute toxicity, Category 4

H312: Harmful in contact with skin.

Skin irritation, Category 2

H315: Causes skin irritation.

Eye irritation, Category 2

H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated exposure, Category 2, hearing organs

H373: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (according to CLP/GHS)

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 + H332 Harmful in contact with skin or if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:
reaction mass of ethylbenzene and xylene

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification (according to CLP/GHS)	Concentration (% w/w)
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0	Flam. Liq. 3; H226 Acute Tox. 4; H332	>=80

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

	01-2119488216-32-XXXX	Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
Substances with a workplace exposure limit :			
(2-methoxymethylethoxy)propanol	34590-94-8 252-104-2 01-2119450011-60-XXXX		$\geq 5 - < 10$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.
Cough
Respiratory disorder
Excessive lachrymation

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

	Erythema Headache Dermatitis Skin disorders See Section 11 for more detailed information on health effects and symptoms.
Risks	: Risk of serious damage to the lungs (by aspiration). irritant effects May be fatal if swallowed and enters airways. Harmful in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water
High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
reaction mass of ethylbenzene and xylene	Not Assigned	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
		GVI	50 ppm 221 mg/m ³	RS OEL
	Further information: This chemical substance can adversely affect the skin., Substance mentioned in indicative exposure limit values in Directive 2000/39 / EC (first list)			
		KGVI	100 ppm 442 mg/m ³	RS OEL
(2-methoxymethylethoxy)propanol	34590-94-8	TWA	50 ppm 308 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		GVI	50 ppm 308 mg/m ³	RS OEL
	Further information: This chemical substance can adversely affect the skin., Substance mentioned in indicative exposure limit values in Directive 2000/39 / EC (first list)			

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- | | | |
|--------------------------|---|---|
| Eye/face protection | : | Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min. |
| Skin and body protection | : | Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work. |
| Respiratory protection | : | In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Ensure adequate ventilation, especially in confined areas. |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | | |
|---------------------------------------|---|-------------------|
| Physical state | : | liquid |
| Colour | : | colourless |
| Odour | : | hydrocarbon-like |
| Melting point/ range / Freezing point | : | No data available |
| Boiling point/boiling range | : | ca. 116 - 140 °C |

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 7 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Flash point : ca. 24 °C
Method: closed cup

Auto-ignition temperature : ca. 432 °C

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : < 6,9 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 7,9993 hPa

Density : ca. 0,86 g/cm³ (20 °C)

Relative vapour density : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful in contact with skin or if inhaled.

Components:

|| reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

|| (2-methoxymethylethoxy)propanol:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: Not classified due to lack of data.

Respiratory sensitisation: Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs (hearing organs) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Components:

reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l
Exposure time: 7 d
Species: Daphnia (water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL
IATA : Paint related material

14.3 Transport hazard class(es)

Class	Subsidiary risks
-------	------------------

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

IATA (Passenger)
Environmentally hazardous : no

IATA (Cargo)
Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

br. 90/2013, 25/2015, 2/2016, 44/2017, 36/2018, 9/2020, : Conditions of restriction for the fol-
57/2022 and 29/2024). lowing entries should be considered:
Number on list 75, 3

REACH - Candidate List of Substances of Very High : None of the components are listed
Concern for Authorisation (Article 59). (=> 0.1 %).

REACH - List of substances subject to authorisation : Not applicable
(Annex XIV)

Regulation (EC) on substances that deplete the ozone : Not applicable
layer

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable
tants (recast)

Regulation (EU) No 649/2012 of the European Parlia- : Not applicable
ment and the Council concerning the export and import
of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of
major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds
(VOCV)
Volatile organic compounds (VOC) content: 100% w/w

Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 100% w/w

Other regulations:

Rulebook on the content of a safety data sheet (Official Gazette No. 11/24)

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

Rulebook on classification, packaging, labeling and advertising of chemicals and products in accordance with UN Globally Harmonized System of Classification and Labelling ("State Gazz. RS", 105/2013, 52/2017, 21/2019, 40/2023).

Law on chemicals ("Off. gazette RS" No. 36/09, 88/10, 92/11, 93/12 and 25/15)

Law on waste management ("Off. Gazette RS" No. 36/2009, 88/2010, 14/2016, 95/2018 - dr. zakon i 35/2023)

Rulebook on categories, testing and classification of waste ("Off. gazette RS" No. 56/2010, 93/2019, 39/2021 and 65/2024)

Rulebook on preventive measures for safe and healthy work during exposure to chemical substances ("Off. gazette RS" No.106/09, 117/17 and 107/21)

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
RS OEL	: Serbia. Occupational Exposure Limits to chemicals at working place (Annex 1)
2000/39/EC / TWA	: Limit Value - eight hours

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025

2000/39/EC / STEL	: Short term exposure limit
RS OEL / GVI	: occupational exposure limit
RS OEL / KGVI	: Short Term Exposure Limit
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H332
Acute Tox. 4	H312
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet

("Sl. glasnik RS", br. 11/24)



Sika® Thinner C

Revision Date 08.01.2025

Version 3.0

Print Date 16.12.2025



Changes as compared to previous version !

RS / EN