

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikalastic®-670 TC

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Srbija d.o.o.
Patrijarha Pavla 1
22310 Šimanovci
Srbija
Telephone : +381 22 21 55 777
Telefax : +381 22 21 55 780
E-mail address of person : ehs@rs.sika.com
responsible for the SDS

1.4 Emergency telephone number

National Toxicology Institute -
+381 11 360 84 40 (toxicologist on duty - 0- 24h)

SECTION 2: Hazards identification

Type of product : Mixture

2.1 Classification of the substance or mixture

Classification (according to regulation governing the classification, packaging and labeling of chemicals)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2, hearing organs	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (according to regulation governing the classification, packaging and labeling of chemicals)

Hazard pictograms :



Signal word : Warning

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

Hazard statements	:	H226	Flammable liquid and vapour.
		H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H335	May cause respiratory irritation.
		H373	May cause damage to organs (hearing organs) through prolonged or repeated exposure.
		H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P260	Do not breathe mist or vapours.
		P264	Wash skin thoroughly after handling.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response:	
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

reaction mass of ethylbenzene and xylene

Pentamethyl piperidylsebacate

Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification (according to regulation governing the classification, packaging and labeling of chemicals)	Concentration (% w/w)
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 25 - < 40

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

		Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 <hr/> M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Cough
Respiratory disorder

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

	Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. irritant effects sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
reaction mass of ethylbenzene and xylene	Not Assigned	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
		GVI	50 ppm 221 mg/m ³	RS OEL
	Further information: This chemical substance can adversely affect the skin., Substance mentioned in indicative exposure limit values in Directive 2000/39 / EC (first list)			
		KGVI	100 ppm 442 mg/m ³	RS OEL

8.2 Exposure controls

Appropriate engineering controls

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth-

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

ods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : various
Odour : characteristic

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 7 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Flash point : ca. 30 °C
Method: closed cup

Auto-ignition temperature : 465 °C

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 7,9993 hPa

Density : ca. 1,25 g/cm³

Relative vapour density : No data available

9.2 Other information

No data available

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Avoid moisture.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Pentamethyl piperidylsebacate:

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs (hearing organs) through prolonged or repeated exposure.

Aspiration hazard

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l
Exposure time: 7 d
Species: Daphnia (water flea)

Pentamethyl piperidylsebacate:

Toxicity to fish : LC50 (Fish): 0,97 mg/l
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1139

IMDG : UN 1139

IATA : UN 1139

14.2 UN proper shipping name

ADR : COATING SOLUTION

IMDG : COATING SOLUTION

IATA : Coating solution

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)
Remarks : Exempted according to 2.2.3.1.5 (Viscous substance exemption)

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E
Remarks : Transport in accordance with 2.3.2.5 of the IMDG-Code

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

REACH Information:	All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.
Rulebook on Bans and Restrictions of Production, Placing on the Market and Use of Chemicals (State Gazette, Nr. 90/2013, 25/2015, 2/2016, 44/2017, 36/2018, 9/2020, 57/2022 and 29/2024)	: Conditions of restriction for the following entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Number on list 75: None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	: Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c	FLAMMABLE LIQUIDS
Volatile organic compounds	: Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC) Volatile organic compounds (VOC) content: 31% w/w Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 31% w/w

Other regulations:

Rulebook on the content of a safety data sheet (Official Gazette No. 11/24).

Rulebook on classification, packaging, labeling and advertising of chemicals and products in accordance with UN Globally Harmonized System of Classification and Labelling ("State Gazz. RS", 105/13, 52/17, 21/19, 40/23).

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

Law on chemicals ("Off. gazette RS" No. 36/09, 88/10, 92/11, 93/12 and 25/15)

Law on waste management ("Off. Gazette RS" No. 36/09, 88/10, 14/16, 95/18 - other law, 35/23).

Rulebook on categories, testing and classification of waste ("Off. gazette RS" No. 56/10, 93/19, 39/21 and 65/24).

Rulebook on preventive measures for safe and healthy work during exposure to chemical substances ("Off. gazette RS" No.106/09, 117/17 and 107/21)

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H361f	: Suspected of damaging fertility.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
RS OEL	: Serbia. Occupational Exposure Limits to chemicals at working place (Annex 1)
2000/39/EC / TWA	: Limit Value - eight hours

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

2000/39/EC / STEL	:	Short term exposure limit
RS OEL / GVI	:	occupational exposure limit
RS OEL / KGVI	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative
according to regulation governing the classification, packaging and labeling of chemicals	:	(REGULATION (EC) No 1272/2008); Rulebook on classification, packaging, labeling and advertising of chemicals and products in accordance with UN Globally Harmonized System of Classification and Labelling ("State Gazz. RS", 105/13, 52/17, 21/19, 40/23).

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikalastic®-670 TC

Revision Date 16.04.2026

Version 1.0

Print Date 16.04.2026

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

RS / EN