

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikalastic®-840 ES Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special system

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Srbija d.o.o.
Patrijarha Pavla 1
22310 Šimanovci
Srbija

Telephone : +381 22 21 55 777

Telefax : +381 22 21 55 780

E-mail address of person responsible for the SDS

1.4 Emergency telephone number

National Toxicology Institute -
+381 11 360 84 40 (toxicologist on duty - 0- 24h)

SECTION 2: Hazards identification

Type of product : Mixture

2.1 Classification of the substance or mixture

Classification (according to CLP/GHS)

Acute toxicity, Category 4

H302: Harmful if swallowed.

Skin corrosion, Sub-category 1B

H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1

H318: Causes serious eye damage.

Specific target organ toxicity - repeated exposure, Category 2

H373: May cause damage to organs through prolonged or repeated exposure.

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (according to CLP/GHS)

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

H314 Causes severe skin burns and eye damage.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P391 Collect spillage.

Hazardous components which must be listed on the label:

Polyoxypropylenediamine
diethylmethylbenzenediamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (according to CLP/GHS)	Concentration (% w/w)
Polyoxypropylenediamine	9046-10-0	Acute Tox.4; H302 Skin Corr.1B; H314 Eye Dam.1; H318 Aquatic Chronic3; H412	>= 60 - < 80
diethylmethylbenzenediamine	68479-98-1 270-877-4 01-2119486805-25- XXXX	Acute Tox.4; H302 Acute Tox.4; H312 Eye Irrit.2; H319 STOT RE2; H373	>= 20 - < 25

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

		Aquatic Acute1; H400 Aquatic Chronic1; H410	
--	--	--	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
In case of eye contact	: Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	: Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: Gastrointestinal discomfort Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	: Health injuries may be delayed. corrosive effects Harmful if swallowed. Causes serious eye damage. May cause damage to organs through prolonged or repeated

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

exposure.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),

breakthrough time >30 min.

Skin and body protection	: Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
Respiratory protection	: No special measures required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: various
Odour	: amine-like

Melting point/range / Freezing point	: No data available
--------------------------------------	---------------------

Boiling point/boiling range	: No data available
-----------------------------	---------------------

Flammability (solid, gas)	: No data available
---------------------------	---------------------

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit	: No data available
--	---------------------

Lower explosion limit / Lower flammability limit	: No data available
--	---------------------

Flash point	: > 101 °C Method: closed cup
-------------	----------------------------------

Auto-ignition temperature	: No data available
---------------------------	---------------------

Decomposition temperature	: No data available
---------------------------	---------------------

pH	: ca. 10,5 (20 °C) Concentration: 100 %
----	--

Viscosity

Viscosity, kinematic	: > 20,5 mm ² /s (40 °C)
----------------------	-------------------------------------

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

Solubility(ies)

Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Vapour pressure	: 0,01 hPa
Density	: ca. 1 g/cm ³ (20 °C)
Relative vapour density	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Components:

Polyoxypropylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 475 mg/kg

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

Acute toxicity estimate: 475 mg/kg
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rabbit): 2.090 mg/kg

diethylmethylbenzenediamine:

Acute oral toxicity : LD50 Oral (Rat): 738 mg/kg

Acute toxicity estimate: 738 mg/kg
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): 2.500 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

: The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated packaging

: 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 2735
IMDG	:	UN 2735
IATA	:	UN 2735

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

14.2 UN proper shipping name

ADR	:	AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylenediamine)
IMDG	:	AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylenediamine)
IATA	:	Amines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	:	8
IMDG	:	8
IATA	:	8

14.4 Packing group

ADR		
Packing group	:	III
Classification Code	:	C7
Hazard Identification Number	:	80
Labels	:	8
Tunnel restriction code	:	(E)
IMDG		
Packing group	:	III
Labels	:	8
EmS Code	:	F-A, S-B
IATA (Cargo)		
Packing instruction (cargo aircraft)	:	856
Packing instruction (LQ)	:	Y841
Packing group	:	III
Labels	:	Corrosive
IATA (Passenger)		
Packing instruction (passenger aircraft)	:	852
Packing instruction (LQ)	:	Y841
Packing group	:	III
Labels	:	Corrosive

14.5 Environmental hazards

ADR		
Environmentally hazardous	:	yes
IMDG		
Marine pollutant	:	yes

IATA (Passenger)

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Rule book on Bans and Restrictions of Production, Placing on the Market and Use of Chemicals (State Gazette, Nr. 90/2013, 25/2015, 2/2016, 44/2017, 36/2018, 9/2020 and 57/2022) (Annex 1) : Conditions of restriction for the following entries should be considered: Number on list 3

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

E2

ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Not applicable

Other regulations:

Rulebook on the content of a safety data sheet (Official Gazette No. 100/11)

Rulebook on classification, packaging, labeling and advertising of chemicals and products in accordance with UN Globally Harmonized System of Classification and Labelling ("Službeni glasnik RS", broj 105/13, 52/2017 i 21/2019).

Law on chemicals ("Off. gazette RS" No. 36/09, 88/10, 92/11, 93/12 and 25/15)

Law on waste management ("Off. Gazette RS" No. 36/09, 88/10, 14/16, 95/18)

Rulebook on categories, testing and classification of waste ("Off. gazette RS" No. 56/10, 93/19 and 39/21)

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Skin Corr. : Skin corrosion
STOT RE : Specific target organ toxicity - repeated exposure

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikalastic®-840 ES Part A

Revision Date 17.01.2024

Version 1.1

Print Date 16.12.2025

ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4	H302
Skin Corr. 1B	H314
Eye Dam. 1	H318
STOT RE 2	H373
Aquatic Chronic 2	H411

Classification procedure:

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

RS / EN