

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-381/-381 ECF Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Flooring system, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Srbija d.o.o.
Patrijarha Pavla 1
22310 Šimanovci
Srbija
Telephone : +381 22 21 55 777
Telefax : +381 22 21 55 780
E-mail address of person : ehs@rs.sika.com
responsible for the SDS

1.4 Emergency telephone number

National Toxicology Institute -
+381 11 360 84 40 (toxicologist on duty - 0- 24h)

SECTION 2: Hazards identification

Type of product : Mixture

2.1 Classification of the substance or mixture

Classification (according to CLP/GHS)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 4	H413: May cause long lasting harmful effects to aquatic life.

2.2 Label elements

Labelling (according to CLP/GHS)

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

		H317	May cause an allergic skin reaction.
		H413	May cause long lasting harmful effects to aquatic life.
Supplemental Hazard Statements	:	EUH071	Corrosive to the respiratory tract.
Precautionary statements	:	Prevention: P261 Avoid breathing mist or vapours. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.	

Hazardous components which must be listed on the label:

Adduct IXA-P (epoxy amine adduct, polymer)
3-aminomethyl-3,5,5-trimethylcyclohexylamine
m-phenylenebis(methylamine)
Cashew, nutshell liq.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification (according to CLP/GHS)	Concentration (% w/w)
---------------	--	---	--------------------------

Adduct IXA-P (epoxy amine adduct,	212580-83-1	Acute Tox. 4; H302	>= 25 - < 40
-----------------------------------	-------------	--------------------	--------------

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

polymer)	Not Assigned	Skin Sens. 1; H317 Aquatic Chronic 4; H413	
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	>= 25 - < 40
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 10 - < 20
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 10 - < 20
2,4,6-tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27-XXXX	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 5 - < 10
Polyoxypropylene diamine	9046-10-0 618-561-0 01-2119557899-12-XXXX	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 2,5 - < 3
Cashew, nutshell liq.	8007-24-7 700-991-6 01-2119502450-57-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

- | | | |
|-------------------------|---|---|
| In case of skin contact | : | Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. |
| In case of eye contact | : | Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing. |
| If swallowed | : | Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|----------|---|---|
| Symptoms | : | Gastrointestinal discomfort
Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms. |
| Risks | : | Health injuries may be delayed.
corrosive effects
sensitising effects

Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye damage.
Causes severe burns.
Corrosive to the respiratory tract. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|------------------------|
| Treatment | : | Treat symptomatically. |
|-----------|---|------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|------------------------------|---|--|
| Suitable extinguishing media | : | In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction. |
|------------------------------|---|--|

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet

("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

and stirring work.

Respiratory protection : No special measures required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid (20 °C)
Colour : yellow
Odour : amine-like

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : ca. 11 (20 °C)
Concentration: 100 %

Viscosity

Viscosity, dynamic : ca. 850 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0,07 hPa

Density : ca. 1,03 g/cm³ (20 °C)

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

Relative vapour density : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Components:

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1.620 mg/kg

Acute toxicity estimate: 1.620 mg/kg
Method: Calculation method

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute toxicity estimate: 4,178 mg/l
Test atmosphere: dust/mist
Method: Calculation method

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

|| 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : Acute toxicity estimate: 1.030 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LD50 Oral (Rat): 1.030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
LD50 (Rabbit): > 2.000 - 5.000 mg/kg

|| m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg
Acute toxicity estimate: 930 mg/kg
Method: Calculation method

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.

Acute toxicity estimate: 1,34 mg/l
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

|| 2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg
Remarks: Harmful if swallowed.
Annex VI - Harmonised
REGULATION (EC) No 1272/2008

|| Polyoxypropylene diamine:

Acute oral toxicity : LD50 Oral (Rat): 2.880 mg/kg

|| Cashew, nutshell liq.:

Acute oral toxicity : LD50 Oral (Rat): 500 mg/kg
Acute toxicity estimate: 500 mg/kg
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): 2.000 mg/kg

Acute toxicity estimate: 2.000 mg/kg

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet

("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

Method: Calculation method

Skin corrosion/irritation

Causes severe burns.

Components:

|| 2,4,6-tris(dimethylaminomethyl)phenol:

Species: Rabbit

Assessment: Corrosive

Method: OECD Test Guideline 404

Assessment: irritating

Remarks: Annex VI - Harmonised

REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

|| 2,4,6-tris(dimethylaminomethyl)phenol:

Species: Rabbit

Assessment: Causes serious eye damage.

Assessment: irritating

Remarks: Annex VI - Harmonised

REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

SECTION 12: Ecological information

12.1 Toxicity

Components:

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l
Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l
Exposure time: 72 h

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l
Exposure time: 72 h

Polyoxypropylene diamine:

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 80 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

ADR : UN 2735
IMDG : UN 2735
IATA : UN 2735

14.2 UN proper shipping name

ADR : AMINES, LIQUID, CORROSIVE, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))
IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))
IATA : Amines, liquid, corrosive, n.o.s.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 8	
IMDG	: 8	
IATA	: 8	

14.4 Packing group

ADR
Packing group : II
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG
Packing group : II
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)
Packing instruction (cargo aircraft) : 855
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosive

IATA (Passenger)
Packing instruction (passenger aircraft) : 851
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosive

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Rule book on Bans and Restrictions of Production, Placing on the Market and Use of Chemicals (State Gazette, Nr. 90/2013, 25/2015, 2/2016, 44/2017, 36/2018, 9/2020 and 57/2022) (Annex 1) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants : Not applicable

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

tants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 28,82% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 28,82% w/w

Other regulations:

Rulebook on the content of a safety data sheet (Official Gazette No. 100/11)

Rulebook on classification, packaging, labeling and advertising of chemicals and products in accordance with UN Globally Harmonized System of Classification and Labelling ("Službeni glasnik RS", broj 105/13, 52/2017 i 21/2019).

Law on chemicals ("Off. gazette RS" No. 36/09, 88/10, 92/11, 93/12 and 25/15)

Law on waste management ("Off. Gazette RS" No. 36/09, 88/10, 14/16, 95/18)

Rulebook on categories, testing and classification of waste ("Off. gazette RS" No. 56/10, 93/19 and 39/21)

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4	H302
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 4	H413

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet

("Sl. glasnik RS", br. 100/2011)



Sikafloor®-381/-381 ECF Part B

Revision Date 26.01.2024

Version 2.0

Print Date 16.12.2025

|| Changes as compared to previous version !

RS / EN