

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikalastic® Metal Primer N Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Primer, Corrosion protection, For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Srbija d.o.o.  
Patrijarha Pavla 1  
22310 Šimanovci  
Srbija  
Telephone : +381 22 21 55 777  
Telefax : +381 22 21 55 780  
E-mail address of person responsible for the SDS : ehs@rs.sika.com

#### 1.4 Emergency telephone number

National Toxicology Institute -  
+381 11 360 84 40 (toxicologist on duty - 0- 24h)

### SECTION 2: Hazards identification

Type of product : Mixture

#### 2.1 Classification of the substance or mixture

##### Classification (according to CLP/GHS)

Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (according to CLP/GHS)

Hazard pictograms :



Signal word : Danger

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

Hazard statements	:	H314 H317 H410	Causes severe skin burns and eye damage. May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH071	Corrosive to the respiratory tract.
Precautionary statements	:	<b>Prevention:</b> P273 P280	Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.
		<b>Response:</b> P303 + P361 + P353 P304 + P340 + P310 P305 + P351 + P338 + P310 P391	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. Collect spillage.

Hazardous components which must be listed on the label:

Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine  
m-phenylenebis(methylamine)  
3-aminomethyl-3,5,5-trimethylcyclohexylamine  
Phenolformaldehyd resin  
Amines, polyethylenepoly-, triethylenetetramine fraction  
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, reaction products with ethylenediamine  
3-aminopropyldimethylamine

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

None known.

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Registration number	Classification (according to CLP/GHS)	Concentration (% w/w)
---------------	--	---	--------------------------

benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317	>= 25 - < 40
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	186321-96-0 606-078-8 01-2119983521-35- XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 10 - < 20
Formaldehyde, polymer with 1,3-benzenedimethanamine and phenol	57214-10-5 500-137-0	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 10 - < 20
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 5 - < 10
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318	>= 3 - < 5

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

		Skin Sens. 1A; H317	
Phenolformaldehyd resin	9003-35-4 500-005-2 01-2120735197-51- XXXX	Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 2,5 - < 5
Amines, polyethylenepoly-, triethyl- enetetramine fraction Contains: 2-(2-aminoethylamino)ethanol <= 0,3 %	90640-67-8 292-588-2 01-2119487919-13- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 1 - < 2,5
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2- (chloromethyl)oxirane, reaction prod- ucts with ethylenediamine	72480-18-3 500-253-1 01-2120766318-46- XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2,5
salicylic acid	69-72-7 200-712-3 01-2119486984-17- XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d	>= 0,5 - < 1
3-aminopropyldimethylamine	109-55-7 203-680-9 01-2119486842-27- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Acute Tox. 4; H312 STOT SE 3; H335	>= 0,5 - < 1

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated  
wounds from corrosion of the skin heal slowly and with difficul-

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.

Risks : May cause an allergic skin reaction.  
Causes serious eye damage.  
Causes severe burns.  
Corrosive to the respiratory tract.  
  
Health injuries may be delayed.  
corrosive effects  
sensitising effects

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

### 5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products

Advice on protection against : Normal measures for preventive fire protection.

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

fire and explosion

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water  
Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),  
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : No special measures required.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : amber  
Odour : characteristic

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 93 °C  
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : 11  
Concentration: 100 %

### Viscosity

Viscosity, kinematic : > 7 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : soluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0,07 hPa

Density : ca. 1,03 g/cm<sup>3</sup> (20 °C)

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

Relative vapour density : No data available

### 9.2 Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

: No hazardous decomposition products are known.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **benzyl alcohol:**

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

LD50 Oral (Rat): 1.200 mg/kg

##### **m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute toxicity estimate: 930 mg/kg  
Method: Calculation method

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Corrosive to the respiratory tract.

Acute toxicity estimate: 1,34 mg/l  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Acute oral toxicity : Acute toxicity estimate: 1.030 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

LD50 Oral (Rat): 1.030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg  
LD50 (Rabbit): > 2.000 - 5.000 mg/kg

### **Amines, polyethylenepoly-, triethylenetetramine fraction:**

Acute oral toxicity : LD50 Oral (Rat): 1.716 mg/kg

Acute toxicity estimate: 1.716 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rabbit): 1.465 mg/kg  
Acute toxicity estimate: 1.465 mg/kg  
Method: Calculation method

### **salicylic acid:**

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg

Acute toxicity estimate: 891 mg/kg  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

### **Skin corrosion/irritation**

Causes severe burns.

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### **Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified due to lack of data.

### **Germ cell mutagenicity**

Not classified due to lack of data.

### **Carcinogenicity**

Not classified due to lack of data.

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT - single exposure**

Corrosive to the respiratory tract.

### **STOT - repeated exposure**

Not classified due to lack of data.

### **Aspiration toxicity**

Not classified due to lack of data.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

##### **benzyl alcohol:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

##### **Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,705 mg/l  
Exposure time: 48 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

##### **m-phenylenebis(methylamine):**

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h

### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l  
Exposure time: 72 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADR** : UN 2735  
**IMDG** : UN 2735  
**IATA** : UN 2735

#### 14.2 UN proper shipping name

**ADR** : AMINES, LIQUID, CORROSIVE, N.O.S.  
(Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine)  
**IMDG** : AMINES, LIQUID, CORROSIVE, N.O.S.  
(Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine)  
**IATA** : Amines, liquid, corrosive, n.o.s.  
(Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine)

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADR</b>	: 8	
<b>IMDG</b>	: 8	
<b>IATA</b>	: 8	

#### 14.4 Packing group

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

### ADR

Packing group : III  
Classification Code : C7  
Hazard Identification Number : 80  
Labels : 8  
Tunnel restriction code : (E)

### IMDG

Packing group : III  
Labels : 8  
EmS Code : F-A, S-B

### IATA (Cargo)

Packing instruction (cargo aircraft) : 856  
Packing instruction (LQ) : Y841  
Packing group : III  
Labels : Corrosive

### IATA (Passenger)

Packing instruction (passenger aircraft) : 852  
Packing instruction (LQ) : Y841  
Packing group : III  
Labels : Corrosive

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

### IATA (Passenger)

Environmentally hazardous : yes

### IATA (Cargo)

Environmentally hazardous : yes

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Country RS 100000058135

14 / 17

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

### Schedules of Toxic Chemicals and Precursors

REACH Information:	All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.
Rule book on Bans and Restrictions of Production, Placing on the Market and Use of Chemicals (State Gazette, Nr. 90/2013, 25/2015, 2/2016, 44/2017, 36/2018, 9/2020 and 57/2022) (Annex 1)	: Conditions of restriction for the following entries should be considered: Number on list 75, 3
Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	: Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	
E1	ENVIRONMENTAL HAZARDS
Volatile organic compounds	: Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 34,12% w/w
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 34,92% w/w

### Other regulations:

Rulebook on the content of a safety data sheet (Official Gazette No. 100/11)

Rulebook on classification, packaging, labeling and advertising of chemicals and products in accordance with UN Globally Harmonized System of Classification and Labelling ("State Gazz. RS", 105/2013, 52/2017, 21/2019, 40/2023).

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

Law on chemicals ("Off. gazette RS" No. 36/09, 88/10, 92/11, 93/12 and 25/15)

Law on waste management ("Off. Gazette RS" No. 36/09, 88/10, 14/16, 95/18)

Rulebook on categories, testing and classification of waste ("Off. gazette RS" No. 56/10, 93/19 and 39/21)

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H361d	: Suspected of damaging the unborn child.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikalastic® Metal Primer N Part B

Revision Date 30.09.2024

Version 1.0

Print Date 16.12.2025

	test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

#### Classification procedure:

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

RS / EN