

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor® Marine Primer-C

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Srbija d.o.o.
Patrijarha Pavla 1
22310 Šimanovci
Srbija
Telephone : +381 22 21 55 777
Telefax : +381 22 21 55 780
E-mail address of person : ehs@rs.sika.com
responsible for the SDS

1.4 Emergency telephone number

National Toxicology Institute -
+381 11 360 84 40 (toxicologist on duty - 0- 24h)

SECTION 2: Hazards identification

Type of product : Mixture

2.1 Classification of the substance or mixture

Classification (according to regulation governing the classification, packaging and labeling of chemicals)

Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (according to regulation governing the classification, packaging and labeling of chemicals)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P261 Avoid breathing mist or vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one (BIT)
2-octyl-2H-isothiazole-3-one (OIT)
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Active ingredient: 1,2-benzisothiazol-3(2H)-one (BIT), 2634-33-5, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 55965-84-9, 2-octyl-2H-isothiazole-3-one (OIT), 26530-20-1. Please use treated articles responsibly.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification (according to regulation governing the classification, packaging and labeling of chemicals)	Concentration (% w/w)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	68610-51-5 271-867-2 01-2119496062-39-XXXX	Repr. 2; H361d Aquatic Chronic 4; H413	>= 0,25 - < 0,5
1,2-benzisothiazol-3(2H)-one (BIT)	2634-33-5	Acute Tox. 4; H302	>= 0,036 - <

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

	220-120-9 01-2120761540-60-XXXX	Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	0,1
bronopol (INN)	52-51-7 200-143-0 01-2119980938-15-XXXX	Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	$\geq 0,0025 - < 0,025$
2-octyl-2H-isothiazole-3-one (OIT)	26530-20-1 247-761-7 01-2120768921-45-XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	$\geq 0,0025 - < 0,025$
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-	55965-84-9 Not Assigned	Acute Tox. 3; H301 Acute Tox. 2; H330	$\geq 0,0002 - < 0,0015$

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

2H-isothiazol-3-one (3:1)	01-2120764691-48-XXXX	Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100
---------------------------	-----------------------	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
See Section 11 for more detailed information on health effects and symptoms.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

Risks : sensitising effects
May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

Personal protective equipment

Eye/face protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	: Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
Respiratory protection	: No special measures required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: white
Odour	: slight
Melting point/freezing point	: ca. 0 °C
Initial boiling point and boiling range	: ca. 100 °C
Flammability	: The product is not flammable.

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit	: Not applicable
Lower explosion limit / Lower flammability limit	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
pH	: ca. 8 (20 °C) Concentration: 100 %

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

Viscosity

Viscosity, kinematic : > 7 mm²/s (40 °C)

Solubility(ies)

Water solubility : completely soluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 23 hPa

Density : ca. 1,02 kg/l (20 °C)

Relative vapour density : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene:

Acute oral toxicity : LD50 Oral (Rat): > 5.001 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.001 mg/kg

1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity : Acute toxicity estimate: 450 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LD50 Oral (Rat): 450 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 0,21 mg/l
Test atmosphere: dust/mist
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LC50: 0,21 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

2-octyl-2H-isothiazole-3-one (OIT):

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l
Test atmosphere: dust/mist
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Assessment : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

SECTION 12: Ecological information

12.1 Toxicity

Components:

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene:

Toxicity to fish (Chronic toxicity) : LC50: > 20 mg/l
Exposure time: 96 d
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: > 20 mg/l
Exposure time: 48 d
Species: Daphnia (water flea)

1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 3 mg/l
Exposure time: 48 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

bronopol (INN):

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

2-octyl-2H-isothiazole-3-one (OIT):

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

12.2 Persistence and degradability

No data available

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic sol-

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

vents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Rule book on Bans and Restrictions of Production, Placing on the Market and Use of Chemicals (State Gazette, Nr. 90/2013, 25/2015, 2/2016, 44/2017, 36/2018, 9/2020, 57/2022 and 29/2024) : Conditions of restriction for the following entries should be considered:
Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Number on list 75:
None of the components are listed
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Not applicable

Other regulations:

Rulebook on the content of a safety data sheet (Official Gazette No. 11/24).

Rulebook on classification, packaging, labeling and advertising of chemicals and products in accordance with UN Globally Harmonized System of Classification and Labelling ("State Gazz.

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

RS", 105/2013, 52/2017, 21/2019, 40/2023).

Law on chemicals ("Off. gazette RS" No. 36/09, 88/10, 92/11, 93/12 and 25/15)

Law on waste management ("Off. Gazette RS" No. 36/09, 88/10, 14/16, 95/18 - other law, 35/2023)

Rulebook on categories, testing and classification of waste ("Off. gazette RS" No. 56/10, 93/19 and 39/21)

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H331	: Toxic if inhaled.
H335	: May cause respiratory irritation.
H361d	: Suspected of damaging the unborn child.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Repr.	: Reproductive toxicity
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association

SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet
("Sl. glasnik RS", br. 11/24)



Sikafloor® Marine Primer-C

Revision Date 08.05.2025

Version 1.0

Print Date 16.12.2025

IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative
according to regulation governing the classification, packaging and labeling of chemicals	:	(REGULATION (EC) No 1272/2008); Rulebook on classification, packaging, labeling and advertising of chemicals and products in accordance with UN Globally Harmonized System of Classification and Labelling ("State Gazz. RS", 105/2013, 52/2017, 21/2019, 40/2023).

Further information

Classification of the mixture:

Skin Sens. 1	H317
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

RS / EN