

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikagard®-2406 Protection Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating, Product is not intended for consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Srbija d.o.o.  
Patrijarha Pavla 1  
22310 Šimanovci  
Srbija

Telephone : +381 22 21 55 777

Telefax : +381 22 21 55 780

E-mail address of person responsible for the SDS : ehs@rs.sika.com

#### 1.4 Emergency telephone number

National Toxicology Institute -  
+381 11 360 84 40 (toxicologist on duty - 0- 24h)

### SECTION 2: Hazards identification

Type of product : Mixture

#### 2.1 Classification of the substance or mixture

##### Classification (according to CLP/GHS)

Flammable liquids, Category 3

H226: Flammable liquid and vapour.

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (according to CLP/GHS)

Hazard pictograms :



# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Isophorondiisocyanate homopolymer  
Hydrocarbons, C9, aromatics

### Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification (according to CLP/GHS)	Concentration (% w/w)
Isophorondiisocyanate homopolymer	53880-05-0	Skin Sens. 1B;	>= 60 - < 80

| Isophorondiisocyanate homopolymer | 53880-05-0 | Skin Sens. 1B; | >= 60 - < 80 |

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

Contains: 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate <= 0,49 %	931-312-3 500-125-5 01-2119488734-24- XXXX	H317 STOT SE 3; H335 (Respiratory sys- tem)	
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35- XXXX [correspond- ing group CAS 64742-95-6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory sys- tem) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 20 - < 25
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29- XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 5 - < 10

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough  
Respiratory disorder  
Allergic reactions

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

Erythema  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.

Risks	: irritant effects sensitising effects
	May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : Water  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed in a dry and well-ventilated

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

areas and containers place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
		GVI	50 ppm 241 mg/m <sup>3</sup>	RS OEL
Further information: Substance mentioned in indicative exposure limit values in Directive 2019/1831/ EC (fifth list)				
		KGVI	150 ppm 723 mg/m <sup>3</sup>	RS OEL

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),  
breakthrough time >30 min.

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

---

Skin and body protection	: Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: yellow
Odour	: solvent-like
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flammability (solid, gas)	: No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit	: 7 %(V)
Lower explosion limit / Lower flammability limit	: 0,8 %(V)
Flash point	: ca. 41 °C Method: closed cup
Auto-ignition temperature	: 415 °C
Decomposition temperature	: No data available
pH	: ca. 7 Concentration: 50 %

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

### Viscosity

Viscosity, dynamic : ca. 1.300 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : immiscible

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 12,4989 hPa

Density : ca. 1,06 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

## 9.2 Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### **Acute toxicity**

Not classified due to lack of data.

##### **Components:**

##### **Hydrocarbons, C9, aromatics:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 23,4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

##### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

##### **Components:**

##### **Hydrocarbons, C9, aromatics:**

Assessment: Repeated exposure may cause skin dryness or cracking.

##### **n-butyl acetate:**

Result: Repeated exposure may cause skin dryness or cracking.

##### **Serious eye damage/eye irritation**

Not classified due to lack of data.

##### **Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified due to lack of data.

##### **Germ cell mutagenicity**

Not classified due to lack of data.

##### **Carcinogenicity**

Not classified due to lack of data.

##### **Reproductive toxicity**

Not classified due to lack of data.

##### **STOT - single exposure**

May cause respiratory irritation.

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified due to lack of data.

### Aspiration toxicity

Not classified due to lack of data.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### Hydrocarbons, C9, aromatics:

Toxicity to algae : (Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9 mg/l  
Exposure time: 72 h

#### n-butyl acetate:

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l  
Exposure time: 72 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

#### Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product	: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	: 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Contaminated packaging	: 15 01 10* packaging containing residues of or contaminated by dangerous substances

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR	:	UN 1866
IMDG	:	UN 1866
IATA	:	UN 1866

#### 14.2 UN proper shipping name

ADR	:	RESIN SOLUTION
IMDG	:	RESIN SOLUTION
IATA	:	Resin solution

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	:	3
IMDG	:	3
IATA	:	3

#### 14.4 Packing group

Country RS 000000122900

11 / 15

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

### ADR

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)  
Remarks : Exempted according to 2.2.3.1.5 (Viscous substance exemption)

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### IATA (Passenger)

Environmentally hazardous : no

### IATA (Cargo)

Environmentally hazardous : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Rule book on Bans and Restrictions of Production, Placing on the Market and Use of Chemicals (State Gazette, Nr. 90/2013, 25/2015, 2/2016, 44/2017, 36/2018, 9/2020 and 57/2022) (Annex 1) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 30% w/w

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 30% w/w

### Other regulations:

Rulebook on the content of a safety data sheet (Official Gazette No. 100/11)

Rulebook on classification, packaging, labeling and advertising of chemicals and products in accordance with UN Globally Harmonized System of Classification and Labelling ("State Gazz. RS", 105/2013, 52/2017, 21/2019, 40/2023).

Law on chemicals ("Off. gazette RS" No. 36/09, 88/10, 92/11, 93/12 and 25/15)

Law on waste management ("Off. Gazette RS" No. 36/09, 88/10, 14/16, 95/18)

Rulebook on categories, testing and classification of waste ("Off. gazette RS" No. 56/10, 93/19 and 39/21)

Rulebook on preventive measures for safe and healthy work during exposure to chemical substances ("Off. gazette RS" No. 106/09, 117/17 and 107/21)

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H317	: May cause an allergic skin reaction.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Flam. Liq.	: Flammable liquids
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
RS OEL	: Serbia. Occupational Exposure Limits to chemicals at working place (Annex 1)
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
RS OEL / GVI	: occupational exposure limit
RS OEL / KGVI	: Short Term Exposure Limit
ADR	: European Agreement concerning the International Carriage of

# SAFETY DATA SHEET

In accordance with the Regulations on the content of the safety data sheet  
("Sl. glasnik RS", br. 100/2011)



## Sikagard®-2406 Protection Part B

Revision Date 11.03.2024

Version 2.1

Print Date 16.12.2025

	Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

RS / EN